Paragon Semiconductor Lighting Technology

PSLT

ParagonLED

Specifications

Product Type : G1L115064-230V22WC65

Issued Date : 05/05/2015

Contents

1. General Description

1-1 Naming Rule

1-2 Outline dimensions

2. Electro-optical characteristics

2-1 Absolute Maximum Rating

2-2 Electro-optical characteristics

2-3 Graphs


2-4 Layout

3. Junction Temperature measurement


4. Reliability Test

1.General Description

(1)Naming rule



(2)Outline Dimensions (Unit : mm / Tolerance: 0.2mm)



Thickness: 1.6±0.2mm

2.Electro-Optical Characteristics

(1)Absolute Maximum Rating

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	21.0~23.0	W
Forward Voltage	V_F	230	V
Operating Temperature	T_{opr}	-40 ~ +105	℃
Storage Temperature	T_{stg}	-40 ~ +105	℃
Power Factor	Pf	>0.85	
Assembly process temperature	T_{sol}	<15%	


(2)Electro-Optical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	V_F	-	-	230	-	V
Color Temperature		V_R=230V	6175	6500	6825	
Luminous Intensity	Φ_v	V_F=230V	1780	1870	1965	Lm
Color rendering	Ra	V_F=230V	70	-	-	CRI


Notice: Operating Voltage of product varies from 210V~250V，users must keep the temperature of Tc point under 105 ℃ (with suitable heat sink), or may cause Serious luminous decay. We DO NOT guarantee of improper use.


(3) Graphs

Spectrum




Candle Power Distribution & Cartesian Coordinate





(4)Layout

3.Junction Temperature Measurement



①Thermal resistance of Junction to Case without heat sink : 10℃/W) 〔Reference Value〕

②Thermal resistance of Case to Ambient Air: Depending on what kind of heat sink users choose. In ideal thermal dissipation situation, the thermal resistance is about 1~2 ℃/W.

4.Reliability Test

Test Item	Test Conditions	Number of failed
High Temperature Storage Test	Tstg= +80℃ , x1,000 hrs	0/20
Low Temperature Storage Test	Tstg= -40℃ , x1,000 hrs	0/20
Continous Light-on Test	Ta= 25℃ , RH=65%, x1,000 hrs	0/20
Boiling Test	Ta= 100℃ , RH=100%, x180mins	0/20
Thermal Cycle Test	-40℃ x 30 mins, 80℃ x 30 mins, 100 cycles	0/20

Measuring Item	Measuring Condition	Judging Criteria of Failure
Forward Voltage	V_F = 230V	> 0 x 1.1
Total Luminous Flux	V_F = 230V	< L x 0.7