AHD車牌辨識攝影機+高功率紅外線投射器 組合包

組合元件

❶ AHD 車牌辨識攝影機: AZC-HDL5210MD-C

❷ 高功率紅外線投射器: H815L

❶



AZC-HDL5210MD-C

❷



YST-H815L



警報模組

組合包特點:

❶ AHD 車牌辨識攝影機: AZC-HDL5210MD-C

- 1920 (H) x 1080 (V) Pan/Tile/Zoom Camera
- 1/2.8" Sony 2.1M STARVIS CMOS Sensor
- Color: 0.02Lux@F1.6, B/W: 0.005Lux@ F1.6
- Optical 10X Zoom: f5-50mm / F1.6
- Push AF & Auto IRIS Zoom Lens
- OSD Menu Control (CoC)
- Powerful WDR & Anti-Headlight (HLC)
- Fog Reduction & 3D/2D Noise Reduction

❷ 高功率紅外線投射器: H815L

- 本體具有通風間隙之雙層遮陽罩 / 可依攝影機需求訂製防護罩長度
- 符合環保ROHS 標準
- 本體上蓋可依據環境因素調整前後間距

AHD攝影機+高功率紅外線投射器 組合包

特點

AHD車牌辨識攝影機: AZC-HD5210BS-C	
Video System	PAL / NTSC Selectable
Image Sensor	1/3" Sony 2.0M STARVIS CMOS Sensor
Resolution	1920(H)x1080(V)
Frame Rates	1920x1080P@25/30fps
Minimum Illumination	Color: 0.02Lux@F1.8, B/W: 0.005Lux@F1.8 IR On: 0Lux@F1.8
Wide Dynamic Range	120dB
Digital Video Output	AHD 1080p
Analog Video Output	CVBS (1.0Vp-p Composite, 75Ω)
Audio	N/A
Mechanical IR Cut Filter	Automatically Switches (Switching Lux Level can be adjusted)
IR LED; Working Distance (Meter)	30 Units (6pcs High Power, 24pcs Hi-Bright, OSRAM LEDs) ; 30-40M
OSD Menu	OSD Control / CoC(Only applied on non-PoC model)
Title	Title (Location)
Day & Night Mode	Color / B&W / Auto / IR Sync
Electronic Shutter	Auto: 1/25(30)~1/30, 000 Sec, Flickerless; Manual: 1/25(30), 1/50(60),1/100(120), 1/240, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/16000, 1/30000 Sec
Auto Gain Control	0~20 Steps
White Balance	ATW / AWB / PWB(Push Lock) / Manual
WDR; BLC; HLC	High (Max 120dB) / Middle / Low / Off; Program; On / Off
Flickerless	PAL 50Hz / NTSC 60Hz / Off
Fog Reduction	Auto / Manual / Off; Level: High / Middle / Low
Dynamic Noise Reduction	High / Middle / Low / Off
Sense Up	On (x2, x4, x8, x16, x32) / Off
Digital Image Stabilizer	N/A
Language	English, Japanese, Traditional Chinese, Simplified Chinese
E-Zoom	8X
Image Setting	Sharpness / Mirror / Flip
Privacy Zone Mask	16 Zones Programmable
Motion Detection	On: Sensitivity, Programmable / Off
Camera Control Interface	CoC
Lens	10X Optical Zoom f5.0mm(Wide)~50mm(Tele), F1.8 to F3.0
Angle of View	H: 49.38°(Wide) ~ 5.30°(Tele)
Minimum Working Distance	1 Meter
Focusing System	Manual / Push AF
Water Resistance	IP66
Power Supply; Consumption	12Vdc ; 6.36W, Option: PoC ; 3.36W
Operation; Storage Temp.	-10°C ~ 50°C; -20°C ~ 60°C
Operation; Storage Humidity	Maximum: RH80%; RH90%
Dimensions	89(DIA) x 168(L)mm
Net Weight	700g

高功率紅外線投射器: H815L	
機種型號	YST-H815L
外觀材質	鋁合金 / 外部螺絲:不鏽鋼
外觀顏色	乳白色或 米白色
警報模組	選購 (可依據環境調整喇叭警報時間, 模組內含微動開關及震動開關)
LED 控制接點	可搭配攝影機之外部控制接點
紅外線角度	15 度 依需求選擇配置
紅外線發光體	12 顆 高亮度22φ 鋁基板 850nm IR LED
紅外線投射距離	15 度→150M
開啟方式	側掀式
紅外線啟動方式	具雙CDS 方式設計,當照度低於10Lux 時,CDS 自動啟動紅外線
高轉速磁浮風扇	YES
玻璃中孔尺寸	外徑53mm / 內徑51mm
防水等級	IP 66
適用鏡頭	2.8~12mm 5~60mm 5~100mm 10~120mm
外觀尺寸	450mm(L) x140mm(W) x 135mm(H)
電流輸出功率	可調式
電源輸入	DC 12V / 3A
工作溫度/濕度	-100C ~ 600C / 95%