

AHD 5M/4M One Cable Starlight

5M / 4M / Starlight / Fixed Lens

	Box		IR Bullet
Model			
Name	SAC-WD2550C	SAC-WDL2531MOC	SAC-WDL2542MOC
Video System	NTSC / PAL Selectable		
Image Sensor	1/2.8" 5.1M STARVIS Sensor		
Video Frame Rate	5M@20fps, 4M@25/30fps		
Minimum Illumination	Color:0.25Lux@F2.0, B/W: 0.15Lux@F2.0, IR On: 0.01Lux		
Video Output	AHD or CVBS Switchable		
IR LED; Working Distance(Meter)	N/A	24pcs 5Ø, 12~15M	24pcs Hi-Bright, 15~20M
OSD Menu	OSD / CoC (Via the coax)		
Digital Day & Night Mode	Color / B&W / Auto / EXT		
Electronic Shutter	1/25(30), 1/50(60), FLK, 1/240, 1/480, 1/1000, 1/2000, 1/5000, 1/10000, 1/50000 sec		
Auto Gain Control	0~15 Steps		
White Balance	ATW / AWC		
WDR; BLC	Auto / Off ; BLC: On / Off / Level		
Dynamic Noise Reduction	3D / 2D		
Language	CHN1, CHN2, ENG, JPN, GER, FRA, ITA, SPA, POL, RUS, POR, NED, TUR		
Image Setting	Mirror / V-Flip / Rotate		
Lens	f2.5mm	f2.8mm	f3.6mm
Water Resistance; Max. Breaking Strength	N/A	IP65	IP66
Power Supply; Consumption	PoC/12Vdc; 2W	PoC/12Vdc; Max.5.6W	PoC/12Vdc; Max.5.6W
Operation; Storage Temp.	-10°C~ 50°C ; -20° C~ 60° C		
Operation; Storage Humidity	Maximum: RH80% ; RH90%		
Dimensions	55(W) x 46(H) x 116(L)mm	133(DIA) x 101mm	87(DIA) x 280mm
Net Weight	250g	700g	700g

Specifications are subject to change without notice.