

AHD 5M/4M One Cable Starlight

5M / 4M / Starlight / Varifocal Lens

	Box		Indoor Dome	IR Vandal Dome		IR Bullet
Model				 ICR IP66	 ICR IK10 IP66	 ICR IP66
Name	SAC-WD2501MOC	SAC-WD2505OC	SAC-WD25021OC	SAC-WDL25031MOC	SAC-WDL25032MOC	SAC-HDL25043MOC
Video System	NTSC / PAL Selectable					
Image Sensor	1/2.8" 5.1M STARVIS Sensor					
Video Frame Rate (Maximum)	5M@20fps, 4M@25/30fps					
Minimum Illumination	N/A	0.08Lux@F1.4, B/W: 0.05Lux@F1.4		0.08Lux@F1.4, B/W: 0.05Lux@F1.4, IR On: 0.001 Lux		
Video Output	AHD or CVBS Switchable					
IR LED; Working Distance(Meter)	N/A			24pcs(Ø5); 15~20M	30pcs(Hi-Bright), 20-25M	30pcs(Hi-Bright), 25-30M
OSD Menu	OSD / CoC (Via the coax)					
Digital Day & Night Mode	Color / B&W / Auto / EXT			Color / B&W / Auto / IR Sync		
Electronic Shutter	1/25(30), 1/50(60), 1/100(120), 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/15000, 1/30000 sec					
Auto Gain Control	0~15 Steps					
White Balance	ATW / AWC					
WDR; BLC	Auto / Off ; BLC: On / Off / Level					
Dynamic Noise Reduction	3D / 2D					
Language	CHN1, CHN2, ENG, JPN, GER, FRA, ITA, SPA, POL, RUS, POR, NED, TUR					
Image Setting	Mirror / V-Flip / Rotate					
Lens Shading Compensation	On / Off					
Lens	CS/C Mount	Built-in Varifocal Lens, f2.8~12mm/F1.4		Built-in Varifocal, f2.8~12mm/F1.4, D/N Lens		
Lens Options	N/A			N/A	N/A	N/A
Water Resistance; Max. Breaking Strength	N/A			IP65	IP66 ; IK10	IP66
Power Supply; Consumption	PoC/12Vdc; 2W			PoC/12Vdc; Max.5.6W	PoC/12Vdc; Max.5.6W	PoC/12Vdc; Max.5.6W
Operation; Storage Temp.	-10°C~ 50°C ; -20° C~ 60° C					-10° C~50°C ; -20°C~60°C
Operation; Storage Humidity	Maximum: RH80% ; RH90%					
Dimensions	120(L) x 56(H) x 67(W)mm	55(W) x 46(H) x 144(L)mm	124(DIA) x 102mm	133(DIA)x101mm	140(DIA) x 112mm	87(DIA) x 280mm
Net Weight	350g	400g	302g	700g	1000g	700g

Specifications are subject to change without notice.