

2M Darklight Camera

H.264 | HDR

Name	SNC-WD2201MD	SNC-WDL223MD	SNC-WDL2203MD	SNC-WDL22043MDV-II
Model	 120dB	 ICR IP66 120dB	 ICR IP66 IK10 120dB	 ICR IP66 120dB
Image Sensor	1/3" SONY 2.1M Darklight CMOS Sensor			
Video Frame Rate	1920x1080@25/30fps, 1280x1024@25/30fps, 1280x720@25/30fps, 720x480@25/30fps			
Video Compression	H.264, MPEG4 and M-JPEG			
Minimum Illumination	Color: 0.015Lux, B/W: 0.008Lux@F1.2	Color: 0.015Lux@F1.2, B/W: 0.008Lux@F1.2, Sense-up: 0.001Lux@F1.2, IR On: 0Lux@F1.2		
IR LED; Working Distance	N/A	24pcs; 15~20M	24pcs Hi-Bright; 15~20M	30pcs Hi-Bright; 20~25M
Protocols	TCP IP, UDP, HTTP, SMTP, FTP, NTP, DNS, DHCP, PPPoE, ARP, UPnP, RTSP, RTP, SNMP, TRAP, Ethernet (RJ-45 Wired 10/100 Base-TX)			
Video Streaming	H.264, MPEG4 and M-JPEG Dual / Triple Streaming			
Lens	N/A	3.5X; f3.0~10.5mm	4X; f2.8~12mm	4X; f2.8~12mm