

名稱	SNC-WD2201MD	SNC-WDL223MD	SNC-WDL2203MD	SNC-WDL22043MDV-II
型號	 120dB	 ICR IP66 120dB	 ICR IP66 IK10 120dB	 ICR IP66 120dB
影像感測器	1/3" SONY 2.1百萬畫素極黑光CMOS影像感測器			
最高影像速率 (幀/秒)	1920x1080@25/30 fps, 1280x1024@25/30 fps, 1280x720@25/30 fps, 720x480@25/30 fps			
影像壓縮	H.264, MPEG4與M-JPEG			
最低照度	彩色: 0.015Lux, 黑白: 0.008Lux@F1.2	彩色: 0.015Lux@F1.2, 黑白: 0.008Lux@F1.2, Sense-up: 0.001Lux@F1.2, 紅外燈開啟: 0Lux@F1.2		
紅外線燈 ; 照射距離	無	24個; 15~20公尺	24個高亮度燈; 15~20公尺	30個高亮度燈; 15~20公尺
協定	TCP IP, UDP, HTTP, SMTP, FTP, NTP, DNS, DHCP, PPPoE, ARP, UPnP, RTSP, RTP, SNMP, TRAP, Ethernet (RJ-45 Wired 10/100 Base-TX)			
影像傳輸	H.264, MPEG4與M-JPEG 碼流/三碼流			
鏡頭	無	3.5倍; f3.0~10.5mm	4倍; f2.8~12mm	4倍; f2.8~12mm