

SNVR-8008ST-2

- 8ch 1080P / 8ch 720P Standalone NVR
- Linux Embedded – Free from PC Crash and Virus Attack
- High throughput for Megapixel Camera Recording
- Local Display with HDMI / BNC / VGA Output
- Digital PTZ and Multi-view
- Web-based Configuration, Live Viewing, Playback
- Auto Search Camera
- Support Peer to Peer Mobile Viewing
- Support external WiFi / 3G Dongle
- Support Video Forwarding



| System | CPU | SoC |
|-----------|-----------------------------|--|
| | System | Standalone NVR |
| | Operating System | Embedded Linux OS |
| | Language | Traditional Chinese, Simplified Chinese, English, Japanese, Thai, Korean, Russian, French, German, Italian, Portuguese, Spanish, Dutch, Turkish, Hungarian, Persian, Polish, Hebrew, Kazakh, Czech, Romanian |
| Video | System Update | Update Firmware via USB /Ethernet |
| | Recording Cameras | 8ch 1080P / 8ch 720P |
| | Video Compression | H.264 |
| | Recording Performance | 1080P:1Mbps~6Mbps, 720P:500Kbps~1Mbps Sub-stream:1Mbps, Max 40Mbps, |
| Audio | Audio&Video Recording | Audio and Video Recording in Synchronization (Depends on IP Camera) |
| Alarm | Alarm In | 4ch |
| | Alarm Out | 1 channel |
| Function | Menu | Can be set via browser or local control ; Local Control |
| | Split screen | 1, 4, 6, 8, 9 |
| | Recording Stream | H.264 |
| | Recording Resolution, Speed | 1080P:30fps, 720P:30fps |
| | Record Mode | Scheduled Record, Manual Record, Dynamic Detection, Alarm Trigger |
| | Video Search | Time Line Search, Event Search |
| | Remote Live View Control | Live View, Preset / Go, PTZ, Remote I/O, Snapshot, Multi-view, 15X Digital PTZ |
| | Video Playback | 1080P:1ch, 720P:4ch simultaneous playback |
| | Video Backup | USB Backup (Flash Drives, USB Hard Disk) |
| Network | Browser | IE 9.0 or Above |
| | Ethernet | 10/100M Auto Negotiation x1 |
| | Supported Protocols | TCP/IP, PPPoE, DHCP, DNS, RTSP, HTTP, SMTP |
| | Video Streaming | 8ch 1080P / 8ch 720P |
| | Audio Streaming | Standard Compression G.711 |
| | User | Support 5 Simultaneous Users |
| | Security | ID/Password Protection, User Access Log |
| | Alarm Event | Event Type:Video Loss, Sensor Triggered, Motion Detection Triggered |
| | Mobile Surveillance | Android, iOS(iPhone/iPad), Windows Mobile, Blackberry, Symbian |
| Interface | Control | RS485 x1 |
| | Network Interface | RJ45 x1 |
| | USB Interface | USB 2.0 x 3 |
| | Video Output | VGA x1, HDMI x1, BNC x1 |
| | Audio | Audio In (RCA) x1 ; Audio Out (RCA) x1 |
| | Hard Disk Drive | SATA x2, each Max. 4TB |
| General | Power Supply | 12Vdc 2.6A |
| | Operation Temperature | -10° C~55° C |
| | Storage Temperature | -10° C~60° C |
| | Operation Humidity | 10%~90% |
| | Dimensions | 345(W)x55(H)x300(D)mm |
| | Net Weight | 2.5kg |
| | Supported IPCam Brand(s) | SHANY, ONVIF |

*Specifications are subject to change without notice..._320074886