

SH-SND-3001, SH-SND-3000, SH-SND-DUAL

- Support RTSP/RTCP/RTP(UDP, TCP) Protocols
- Support HDMI
- Instant Decode, Delay<500ms
- Support History Decode
- Support H.264
- Split Screen 4ch(1080P)/9ch(720P)/16ch(D1)



Model	SH-SND-3001	SH-SND-3000	SH-SND-DUAL
Network Protocols	TCP/UDP/DHCP/HTTP/RTSP/RTCP/RTP		
Dial Mode	PSTN/ADSL/DDN/VPN		
Ethnernet Port	100Mbps x 1	100Mbps x 1	1000Mbps x 2
Video	HDMI, YPbPr, BNC , 3.5mm TRS	HDMI, CVBS, YPbPr	HDMI x 2, BNC x 2
Display Mode	1080P (1920x1080), 720P (1280x720), FullD1 (720x576)		
Split Screen	1 (1920x1080) / 4 (1280x720) / 9 (D1) / 16 (D1)		
Decoding	H.264	H.264	H.264
FPS	1~30	1~25	1~25
Bitrate	0.5Mbps~10Mbps	500kbps-8M/1 card for 2ch,Max 24ch	0.5Mbps~10Mbps
Power	AC220V 180W	DC 12V 30W	AC220V 180W
Work Temperature	-10°C~55°C ; -10°C~60°C	-10°C~55°C ; -10°C~60°C	-10°C~55°C ; -10°C~60°C
Work Humidity	10%~90%	10%~90%	10%~90%
Dimension	132mm x 182mm x 34mm	482mm x 315mm x 178mm	202.5mm x 182.1mm x 34.2mm
Net weight	1.2kg	5kg	1kg

