


SAVR-T6108ST-A2M

Standalone AHD/TVI Hybrid Recorder

- AHD/TVI: 1080P/720P & Analog 1080P/720P/960H/D1 Inputs
- Industry - leading Performance in Recording, Playback and Networking
- Maximum up to 240fps recording with 1080p30
- Dual Stream Support for remote access
- Bi - Directional Audio
- Remote Access through Web, CMS, Mobile App (Android & iOS)
- Easy Data Export via USB Drive, Webpage and USB External HDD
- Search Control by Date/Time, Alarm, and Channel Search



System	Operating System	Embedded Linux
	Operations	Live, Recording, Playback, Backup & Remote access
	Control Mode	USB mouse, Webpage, CMS
Video	Input	AHD/TVI: 8CH 1080P/720P Analog: 8CH 1080P/720P/960H/ D1
	Output	1x HDMI, 1xVGA
	Dual Stream	Support
	Frame Rate	Main stream: 30 fps (NTSC)/25 fps (PAL); Sub stream: 30 fps (NTSC)/25 fps (PAL)
Audio	Input	4 x RCA
	Output	1 x RCA
	2-way Audio	Support
Display	Display mode	Full screen / Multi-screen / Sequence
	OSD	GUI
	Remote View	Via IE Web Viewer, CMS
	Mobile View	iOS / Android
Recording	Recording Mode	Continuous, scheduled, alarm, motion
	Recording Capability	480fps@720P, 240fps@1080P
	Pre Recording	5 seconds
	Post Recording	Max. 255 seconds
Network	Support	TCP / IP, SMTP, DHCP, DDNS, PPPoE, UDP, SSL, RTP, RTSP, NTP
	Ethernet	1x10/100 Mbps
Playback & Backup	Display Mode	Full Screen / Multi-screen
	Playback Capability	8 ch simultaneous playback
	Playback Control	Play/Pause/Step/Fast forward/Rewind/ Fast rewind
	Search Control	By Date/Time, Events, Channel
	Export	Through USB / Webpage / CMS
	Internal Storage	2 SATA Ports , Up to 4TB capacity for each
I/O	USB	2; 1 for mouse control and 1 for backup
	Alarm	8 ch simultaneous playback
	RS485	1; Support Pelco D, Pelco P
Control Mode	Watermark	Yes
	User Privilege	3 Levels of User Access Support
	Power	12V DC
	Temperature	0° C ~ 40° C
	Dimension	420(W)x65(H)x305(D) mm± 5mm

*Specifications are subject to change without notice.