AHD 1080P **Darklight** One Cable

1080P / Darklight / CoC Control

	BOX		Indoor Dome	IR Vandal Dome	IR Bullet
Model					
Name	**SAC-WD3201MDSOC**	**SAC-WD3205DOC**	**SAC-WD32021DOC**	**SAC-WD32031MDOC**	**SAC-WD32043MDOC**
Video System	NTSC / PAL Selectable				
Image Sensor	2.1M Sony 2nd Generation STARVIS Sensor (Darklight Level)				
Video Frame Rate (Maximum)	1920X1080P@25/30fps				
Minimum Illumination	Color: 0.02, B/W: 0.01			Color: 0.02, B/W: 0.01@F1.4, IR On: 0 Lux	
Video Output	AHD or CVBS Switchable				
IR LED; Working Distance(Meter)	N/A			24pcs(Ø5); 15~20M	30pcs Hi-Bright (OSRAM LEDs), 20-25M
OSD Menu	OSD / CoC (Via the Coax)				CoC (Via the Coax)
Day & Night Mode	Color / B&W / Auto / External			Color / B&W / Auto / IR Sync	
Auto Electronic Shutter	1/25(30) ~1/30, 000 Sec; Flickerless				
Manual Electronic Shutter	1/25(30), 1/50(60), 1/100(120), 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/15000, 1/30000 Sec				
White Balance	ATW / AWB / PWB(Push Lock) / Manual				
WDR; BLC; HLC	Hi / Middle / Low / Off ; Program ; On / Off				
Fog Reduction	Auto / Manual / Off ; Level: High / Middle / Low				
DNR	2D/3D DNR; High / Middle / Low / Off				
Language	English, Japanese, Traditional Chinese, Simplified Chinese				
Image Effects	Sharpness / Mirror / Flip / Motion				
Privacy Zone Masks	16 Zones Programmable				
Automatic IRIS; Connector	N/A	DC Iris			
Lens	CS/C Mount	Built-in Varifocal Lens, f2.8~12mm/F1.4	Built-in Varifocal Lens, f2.8~12mm/F1.4	Built-in Varifocal, f2.8~12mm/F1.4, D/N Lens	Built-in Varifocal f2.8~12mm/F1.4, D/N Lens
Water Resistance; Max. Breaking Strength	N/A			IP65	IP66
Power Supply; Consumption	PoC/12Vdc: 3.36W	PoC/12Vdc: 3.36W	PoC/12Vdc; 3.36W	PoC/12Vdc; Max.5.6W	PoC/12Vdc; Max.5.6W
Operation; Storage Temp.	-10° C~50° C ; -20° C~60° C				
Operation; Storage Humidity	Maximum: RH80%; RH90%				
Dimensions	62(W) x 56(H) x 120(L)mm	55(W) x 46(H) x 144(L)mm	124(DIA) x 102mm	133(DIA)x101mm	87(DIA) x 280mm
Net Weight	350g	400g	302g	700g	640g

Specifications are subject to change without notice.