SNC-HD6201MD

2M Darklight, HDR, Box IP Camera

- Full HD 1920x1080P @ 25/30fps
- 2.1M Sony 2nd Generation STARVIS Senor (Darklight Level)
- Color: 0.01, B/W: 0.005, IR On: 0 Lux @ F1.4
- True WDR up to 120dB
- 2D/3D Smart DNR & Sense up
- Fog Reduction Auto/Manual Mode
- Support PoE or DC12V
- Shutter Mode (AUTO / MANUAL)
- Mechanical IR Cut Filter (ICR)




Video	Image Sensor	1/2.8" 2.1M Sony 2nd Generation STARVIS Senor (Darklight Level)
	Multi-Streaming	**Main Stream**: 1920 * 1080@25/30fps, 1280*720@25/30fps **Sub-Stream:** 1920 * 1080@25/30fps, 1280*720@25/30fps, 704*576@25/30fps, 704*480@25/30fps, 352*288@25/30fps, 352*240@25/30fps **3rd Stream**: 704*576@25/30fps, 704*480@25/30fps, 352*288@25/30fps, 352*240@25/30fps
	Video Compression	H.265, H.264 & MJPEG, 3 kinds of compressed streaming
	Mechanical IR Cut Filter (ICR)	Yes
	Minimum Illumination	Color: 0.1Lux@F1.4, White Light LEDs On: 0 Lux
	Wide Dynamic Range	120dB
	LEDs; Working Dist.	N/A
	ICR	Yes
Function	Day & Night	Day / Night: Auto Smart On, ON, Off Programmable
	Auto Electronic Shutter	Auto 1/25(30)~1/30,000 sec
	White Balance	AWB / ATW / PWB(Push Lock) / Manual
	WDR & BLC Functions	Off/ HLC / D-WDR / WDR / BLC
	DNR	2D/3D Smart DNR
	Text Overlap	Support Channel, Date/Time/Bit Rate, Position Adjustable
	ROI	4 Zones
	Privacy Zone Mask	4 Zones
	Motion Detection	4 Zones
Network	Bit Rate	32Kbps-20Mbps Supported CBR,VBR & QP
	Intelligent Video (Option)	Support: Defocus & Cover Optional: Scene Change, Direction Detection, Tripwire Detection, Virtual Fence, Loitering, Abandoned Object Detection, Missing Object
	Protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
	ONVIF Compatibility	ONVIF Profile S, CGI
	Alarm Trigger	File upload via FTP and e-mail / Notification via e-mail, HTTP
	Audio In/Out	1 Line in (5V/0.1A) / 1 Line Out
	Alarm In/Out	1/1
	Day & Night In/Out	N/A
General	Memory Slot	N/A
	Water Resistance	N/A
	Max. Breaking Strength	N/A
	Power Supply ; Consumption	DC12V/ PoE; 5.5W
	Operation; Storage Temp.	-10°C ~ 50°C ; -20°C ~ 60°C
	Operation; Storage Humidity	Maximum: RH80%; RH90%
	Dimension	94(W) x 86.5(H) x 290.6 (L)mm
	Net Weight	320g
	Others	



Dimensions

Tol: ±0.5 Unit: mm



Options

*Specifications are subject to change without notice._0862_v02_180523.