SAVR-H8208ST-AHL1

- AHD / TVI / IP Hybrid Recorder
- HD Analog Input Max to 5MP
- IP Input Max to 5MP
- H265 / H264 Video Compression
- VGA / HDMI 4K2K Display
- Multiplex Operation / Live / Record / Palyback / Network / Backup
- Synchronous Playback 8CH





Video Compression		H.265 / H.264
Video System		NTSC / PAL
Operation System		Linux (Embedded)
Analog Video - Input / Output		8CH Inputs / VGA and HDMI Output
IP Video Input		4CH, (only IP up to 12CH)
Composite Video Input		up to 8CH (Analog Video + IP Video)
Audio Input / Output		8CH Inputs / 1CH Output (RCA)
Display	Resolution	Analog : 5MP - Lite : 20fps / 4MP - Lite : 30 fps / 3MP : 18fps / 1080P / 720P / 960H : 30fps IP : 5MP / 4MP / 3MP/1080P / 720P
	Feature	1 / 4 / 6 / 8 / 9 / S.E.Q.
Record	Resolution	Analog : 5MP - Lite / 4MP - Lite / 3MP / 1080P / 720P / 960H IP : 5MP / 4MP / 3MP/1080P / 720P
	Speed	Analog : 5MP - Lite : 15fps (each ch) 4MP - Lite : 18fps (each ch) 3MP : 10fps (each ch) 1080P : 15fps (each ch) 720P : PAL : 25fps (each ch) / NTSC : 30fps (each ch) IP : PAL : 25fps (each ch) / NTSC : 30fps (each ch)
IP - Recording Bandwidth (Maximum Input Bandwidth)		16Mbps ~ 48Mbps (default is 16Mbps, decrease one Analog channel can increase 4Mbps)
Maximum Output Brandwidth		64Mbps
Maximum Decode Performance		1080P : 120fps
Recording Mode		Continuous / Manual / Motion Detect
Synchronous Playback		8CH
Network Type		Lan, DHCP, and DDNS
HDD Interface		1SATA HDD, up to 6TB
Multiplex Operation		Live Display, Record, Playback, Backup and Network
USB		2 x USB (for Mouse and Backup / Upgrade)
Sensor & Alarm I / O		8CH Inputs / 1CH Output
PTZ Control		Yes (RS485)
Mobile Surveillance		Support Mobile Phones based on iPhone and Android operation system
VGA / HDMI		1024*768,1280*720,1280*1024,1440*900,1920*1080 (1080P),2560*1440 (2K),3840*2160 (4K)
Power Supply		DC 12V / 2A
Dimension (W x D x H)		300mm X 227mm X 53mm
Working Temperature		-10°C ~ +55°C
Working Humidity		10% ~ 90%
Weight		1030g