

	Indoor Dome	IR Vandal Dome	IR Bullet	
Model		 ICR IP66	 ICR IP66	 ICR IP66 Anti-Spider
Name	SAC-HD7502MV	SAC-HDL75031MV	SAC-HDL75047MV	SAC-HDL75048MV
Video System	NTSC: 5M@20fps, 4M@30fps, 1080P@30fps; PAL: 5M@20fps, 4M@25fps, 1080P@25fps Selectable			
Image Sensor	1/2.8" Sony 5M Starvis Sensor			
Video Frame Rate	NTSC: 5M@20fps, 4M@30fps, 1080P@30fps; PAL: 5M@20fps, 4M@25fps, 1080P@25fps Selectable			
Minimum Illumination	Color: 0.05 Lux B/W:002 Lux @ F1.4	Color 0.05Lux, B/W 0.02 Lux, IR On: 0 Lux @ F1.4		
Video Output	4M (Deafulst), 5M or 1080P Selectable			
IR LED; Working Distance	N/A	21pcs(Hi-Bright), 15-20 M	30pcs(Hi-Bright), 20-25 M	36pcs(Hi-Bright); 25-30M
OSD Menu	OSD / CoC			
Day & Night Mode	Color / B&W / Auto / IR Sync			
Electronic Shutter/Filckless	Auto: 1/25 (30) ~ 1/30,000 Sec; Day/Night Self-Defined Manual Shutter: 1/30(25), 1/60(50), Flickerless 1/120(100), 1/300, 1/350, 1/400, 1/450, 1/500, 1/180(150), 1/240(200), 1/250, , 1/600, 1/750, 1/1000, 1/1,500, 1/2,000, 1/4,000, 1/8,000, 1/16,000, 1/30,000			
White Balance	Indoor / Outdoor / ATW / AWB / AWC / Manual			
HDR (WDR) D-WDR; BLC; HLC	HDR Max 120dB, Window WDR, D-WDR: High / Middle / Low; BLC: High / Middle / Low / Off ; HLC: On / Off			
Fog Reduction	Auto / Manual / Off; Level: High / Middle / Low / Off			
Dynamic Noise Reduction	3DNR / 2DNR, High / Middle / Low / Off			
Sense Up	On (x2, x4, x8, x16, x32) / Off			
Language	English, Japanese, Traditional Chinese, Simply Chinese			
Image Setting	Sharpness / Mirror / Flip			
Privacy Zone Mask	16 Zone Programmable			
Motion Detection	On: Sensitivity, Programmable / Off			
Lens Shading Compensation	On / Off			
Lens	f2.8-12mm Motorized Zoom, D/N			
Water Resistance Vandal Proof	N/A	IP66	IP66	IP66
Power Supply; Consumption	12Vdc; Max.3.6W	12Vdc; Max.5W	12Vdc; Max.5.4W	12Vdc; Max.5.8W
Operation; Storage Temp.	-10°C~ 50°C; -20° C~ 60° C			
Operation; Storage Humidity	Maximum: RH80%; RH90%			
Dimension(mm)	140(Dia) x 112	133(Dia) x101	86(Dia) x 315	94(W) x 86.5(H) x 290.6(L)
Net Weight	500g	700g	850g	1320g

Specifications are subject to change without notice.