AHD 5M/4M Starlight

5M (4M) / Starlight / HDR / Fisheye & 4X Zoom /CoC

	Fisheye	Indoor Dome	IR Vandal Dome	IR Bullet	
Model					
Name	**SAC-HDL75034M**	**SAC-HD7502MV**	**SAC-HDL75031MV**	**SAC-HDL7504MV**	**SAC-HD75048MV**
Video System	NTSC: 5M@20fps, 4M@30fps, 1080P@30fps; PAL: 5M@20fps, 4M@25fps, 1080P@25fps Selectable				
Image Sensor	1/2.8” Sony 5M Starvis Sensor				
Video Frame Rate	NTSC: 5M@20fps, 4M@30fps, 1080P@30fps; PAL: 5M@20fps, 4M@25fps, 1080P@25fps Selectable				
Minimum Illumination	Color: 0.08 Lux, B/W: 0.05 Lux, IR On: 0 Lux @F2.0	Color: 0.05 Lux, B/W:002 Lux @ F1.4	Color: 0.05Lux, B/W 0.02 Lux, IR On: 0 Lux @ F1.4		
Video Output	4M (Deafult), 5M or 1080P Selectable				
IR LED; Working Distance	6pcs Hi-Power Array; 10-15 M	N/A	21pcs(Hi-Bright); 15-20 M	6pcs Hi-Power Array; 20-25M	36pcs(Hi-Bright); 25-30M
OSD Menu	OSD / CoC				
Day & Night Mode	Color / B&W / Auto / IR Sync				
Electronic Shutter/Filckless	Auto: 1/25 (30) ~ 1/30,000 Sec; Day/Night Self-Defined Manual Shutter: 1/30(25), 1/60(50), Flickerless 1/120(100), 1/300, 1/350, 1/400, 1/450, 1/500, 1/180(150), 1/240(200), 1/250, , 1/600, 1/750, 1/1000, 1/1,500, 1/2,000, 1/4,000, 1/8,000, 1/16,000, 1/30,000				
White Balance	Indoor / Outdoor / ATW / AWB / AWC / Manual				
HDR (WDR) D-WDR; BLC; HLC	HDR Max 120dB, Window WDR, D-WDR: High / Middle / Low; BLC: High / Middle / Lo;wH/LOC:ffOn / Off				
Fog Reduction	Auto / Manual / Off; Level: High / Middle / Low / Off				
Dynamic Noise Reduction	3DNR / 2DNR, High / Middle / Low / Off				
Sense Up	On (x2, x4, x8, x16, x32) / Off				
Language	English, Japanese, Traditional Chinese, Simply Chinese				
Image Setting	Sharpness / Mirror / Flip				
Privacy Zone Mask	16 Zone Programmable				
Motion Detection	On: Sensitivity, Programmable / Off				
Lens Shading Compensation	On / Off				
Lens	2.1mm/F2.0	f2.8-12mm Motorized Zoom, D/N			
Water Resistance Vandal Proof	N/A	N/A	IP66	IP66	IP66
Power Supply; Consumption	12Vdc; Max 6W	12Vdc; Max 3.6W	12Vdc; Max 5W	12Vdc; Max 3.6W	12Vdc; Max 5.8W
Operation; Storage Temp.	-10°C~ 50°C; -20° C~ 60° C				
Operation; Storage Humidity	Maximum: RH80%; RH90% ; Maximum: RH80%; RH90%				
Dimension(mm)	120mm (D) x 55mm (H)	140(Dia) x 112	133(Dia) x101	85 (Dia) x 210	94(W) x 86.5(H) x 290.6(L)
Net Weight	310g	500g	700g	450g	1320g

Specifications are subject to change without notice.