



| SPECIFICATIONS                   |              | QAX-8012DSP  |  |
|----------------------------------|--------------|--------------|--|
| Power Output@4Ω(DC14.4V)         |              | 25W*8        |  |
| Power Output@2Ω(DC14.4V)         |              | 35W*8        |  |
| Power Output@1Ω(DC14.4V)         |              | /            |  |
| Power Output@4Ω Bridged(DC14.4V) |              | /            |  |
| THD(1KHz)                        |              | ≤0.05‰       |  |
| Frequency Response               |              | 20HZ-20KHZ   |  |
| S/N Ratio                        |              | ≥110dB       |  |
| Stereo Separation                |              | 55dB         |  |
| Input Sensitivity                |              | /            |  |
| Damping Factor                   |              | 150          |  |
| Input Impedance                  |              | 22K          |  |
| Idle Current                     |              | 1A           |  |
| Crossover                        | LP(12dB/Oct) | /            |  |
|                                  | HP(12dB/Oct) | /            |  |
| Remote Voltage                   |              | /            |  |
| Bass boost(45Hz)                 |              | /            |  |
| DC Offset                        |              | 10MV         |  |
| Power Supply Regulation          |              | 10V-15V      |  |
| Fuse Rating                      |              | 25A          |  |
| Bi Color LED Indicator           |              | /            |  |
| Dimension(WxHxD)                 |              | 180x50x210MM |  |

