



SPECIFICATIONS	QAX-4075	QAX-1800	
Power Output@4Ω(DC14.4V)	75W*4	300W	
Power Output@2Ω(DC14.4V)	125W*4	450W	
Power Output@1Ω(DC14.4V)	/	820W	
Power Output@4Ω Bridged(DC14.4V)	200W*2	/	
THD(1KHz)	≅ 0.05‰	≅ 0.05‰	
Frequency Response	20HZ-39KHZ	20HZ-250HZ	
S/N Ratio	≧ 91dB	≧ 91dB	
Stereo Separation	55dB	/	
Input Sensitivity	0.2V-4V	0.1V-4V	
Damping Factor	150	150	
Input Impedance	22K	22K	
Idle Current	0.5A	1.35A	
Crossover	LP(12dB/Oct)	40-400HZ	40HZ-250HZ
	HP(12dB/Oct)	40-400HZ	20HZ-50HZ
Remote Voltage	/	/	
Bass boost(45Hz)	12dB	12dB	
DC Offset	10MV	30MV	
Power Supply Regulation	10V-15V	10V-15V	
Fuse Rating	25A*2	30A*3	
Bi Color LED Indicator	/	/	
Dimension(WxHxD)	180x50x210MM	180x50x210MM	

