DST Captive Fastener ☐18.7

1-041.09DST



Advantages

- With DIRAK-SNAP-Technology for joining of flat metal sheets and securely latching doors and covers.
- For cutout ☐18.7.
- Meets machinery directive 2006/42EC.
- After pre-assembly the concern of losing, dropping or misplacing hardware is eliminated.
- Vibration-proof.
- Tool-less installation.
- Pressed into the front panel (sheet thickness max. 3mm) and permanently secured by the U-shaped spring (1.).
- Can be disconnected from the rear panel from the front with the tool for uninstallation 292-0312.83-00000.
- One-piece.

Material

- **Housing and Snap wedges:** zinc die, zinc plated
- **U-shaped spring:** AISI 301


Remarks

2. installation
3. installed
4. removal

Removal: by turning the tool for uninstallation counter clockwise the SNAP wedges are drawn back. The U-shaped spring holds the Fastener captive in the front panel.
Oblong hole possible in the rear panel, for tolerance adjustment.
The (S) dimension indicates the total thickness of the sheet metal panels.

Fastener

	Product number	Clamping range (S)	Installation type	Delivery Unit
a)	294-8004.00-00001	11.5 - 11.8 mm	tool-less	10 pcs.


a)
□26 [1.024]
28 [1.102]
4 [0.157]
34.2 [1.346]
□18.5 [0.728]
1.
□18.7 +0.2 [0.736]
s
2.
3.
4.
b)
max. 3