



4-185 Hinge Pr05 180°



Advantages

- For surface mounted doors for adjacent cabinets.
- Hinge partly visible.
- Door bending 25mm.
- RH /LH application.
- 180° Opening angle.

Materials

- **Frame- and door-part:** zinc die, chrome plated or black
- **Washer:** brass, nickel plated
- **Pin:** steel, zinc plated
- **Fastening washer:** steel, zinc plated

Remarks

(S) Door-thickness min 1.5 - max. 2mm
for door thickness (S) 1.5mm x= 12mm
for door thickness (S) 2 mm x= 15mm
1. washer
2. fastening washer



Hinge, zinc die, black

	Part Number	Frame-part	cutout in frame	Material pin	Installation type	Delivery Unit
a)	212-9038.00-00000	with countersunk holes for M6	Ø6	steel, zinc plated	screw-on	10 pcs.
b)	212-9037.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	steel, zinc plated	screw-on	10 pcs.

Hinge, zinc die, chrome plated

	Part Number	Frame-part	cutout in frame	Material pin	Installation type	Delivery Unit
a)	212-9088.00-00000	with countersunk holes for M6	Ø6	steel, zinc plated	screw-on	10 pcs.
b)	212-9050.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	steel, zinc plated	screw-on	10 pcs.

Assembly options

6-041 Countersunk Screws and Hexagon Nuts

